


PES  
RHBE RMB  
PBM PBM

# GENERAL ELECTRIC COMPANY

SCHENECTADY, N. Y., U. S. A.

PLEASE INITIAL AND  
RETURN PROMPTLY TO  
  
FOR FILING

DATA FOLDER No. 72164

Title Oscillographic Method of Measuring Positive Grid  
Characteristics

By

Electronic Tube Engineering Div.

Information prepared for Electronic Tube Engineering Division

Tests made by

Information prepared by C. W. Bleichner - S. G. Ringland

Countersigned by

Date Sept. 1, 1943

This folder is the property of the General Electric Company, and must not be retained except by special permission, or be used directly or indirectly in any way detrimental to the interest of the Company.

OSCILLOGRAPHIC METHOD OF MEASURING  
POSITIVE GRID CHARACTERISTICS

Electronic Tube  
Engineering Division

September 1, 1943

Introduction

This Data Folder supersedes #64587, with the same title, prepared by O. W. Livingston. For this reason, much of the theory and discussion are taken directly from the above-mentioned data folder. Some of the original information, which is no longer necessary, has been eliminated and new information added to cover operation of the rebuilt set.

Considerable difficulty has been experienced in the past in obtaining positive grid characteristics of high-vacuum triodes since tube dissipation while taking these points is so high that the destruction of the tube is likely to take place if the power is left on sufficiently long to read a standard meter.

To obviate this difficulty, tests have been made in which the power is applied for only a short time and oscillograms taken on all the essential data. This method, however, requires considerable calculation from the oscillograms obtained and in many cases errors or peculiar results in the tests are not noticed until the calculations are made which may be sometime after the tests and the test setup may be no longer available. The method used in these tests, we believe, overcomes many of the difficulties involved in these former methods. It is essentially a point-to-point method in which each point on the desired characteristic is obtained separately and can be read directly and plotted as the test progresses. In this way any errors may be checked immediately when the work is completed. No further calculation is necessary since the curves are immediately available.

Theory and Method of Test

Fig. 2 (T-938567) shows the schematic diagram of the test setup. Fundamentally, the operation is as follows. The plate supply condenser  $C_1$  and the grid supply condenser  $C_2$  are charged to a predetermined voltage through their respective rectifier tubes,  $VP_1$  and  $VP_2$ , and transformers,  $T_3$  and  $T_4$ . When the switch  $S_1$  is thrown to the discharge position, an impulse generated in the grid transformers  $T_7$  and  $T_8$  "trips" the thyretrons  $VP_3$  and  $VP_4$  simultaneously applying potential to both the grid and anode. The wave shape of this voltage is similar to that shown in Fig. (a), being essentially the wave shape of a condenser discharge. Since both the grid and anode potentials have this same shape, the instantaneous grid and plate currents at the start of the phenomenon correspond to the values normally obtained with the peak values of grid and plate voltage. The plate current in general has the shape shown in Fig. (a) and the peak value of this

current is normally read by observing the drop across  $R_{13}$  and/or  $R_{11}$  with a cathode-ray oscillograph. Under some conditions, the grid current has the shape of Fig. (a), but under certain other conditions may assume the shape of Fig. (b); in which case, the current at the beginning of the phenomenon is the desired peak current. Again, the grid current may go negative, in which case the negative peak is observed and recorded. It is important in this method that the decay of both grid and plate voltages be sufficiently slow that small errors in firing time of  $VT_3$  and  $VT_4$  do not cause appreciable error. For this reason, the capacities  $C_1$  and  $C_2$  are adjustable in steps.

Calibration curves of the output voltages across the potentiometers  $R_7$ - $R_9$  and  $R_8$ - $R_{10}$  against voltages on the primaries of the supply transformers are included in this report. It is advisable actually taking test data to check this calibration by substituting a known resistance for the tube load and checking a few points on the curves. By means of the calibration curves it is possible to set the grid voltage at some predetermined value, say plus 300 volts, and then vary the plate voltage over the operating range to secure the desired characteristic data.

In some cases, it is further desirable to add additional "bleeder" resistance across the voltage potentiometers, particularly in the case of low or negative currents, which sometimes occur in the grid circuit, in order to insure reliable firing of the thyretrons. Oscillations sometimes occur and are readily observed on the oscillograph when the entire wave shape is being scanned by means of the conventional sweep. In general, oscillations are caused by excessive length or improper placement of the leads connecting the tube under test to the test setup. Small condensers (small compared to  $C_1$  and  $C_2$ ) connected between grid and cathode and plate and cathode may be helpful. In taking readings, it is sometimes convenient to turn off the sweep circuit and simply read the peak, but whenever this is done the sweep should be used from time to time to determine whether or not oscillations are present and, in the case of the grid current, whether or not the peak value is the correct point to read.

#### Operation of the Revised Setup (Fig. 1 T-983567)

1. Set up proper ratios on voltage dividers  $R_7$ - $R_9$  and  $R_8$ - $R_{10}$ , and set suitable series resistors in plate and grid leads  $R_{11}$ - $R_{13}$  and  $R_{12}$ - $R_{14}$ .
2. Close 220 volt AC main switch. (20)
3. Close non-interlocked 110 v. supply. (21)  
Allow five minutes for FG-41 filaments to heat.
4. Close 125 volt DC main supply. (22)
5. Close 110 volt AC interlocked supply. (23)

6. Adjust the filament voltage of the tube under test.
7. After the interlock has been closed, grid and plate voltages, grid and plate currents, may be read by placing the oscilloscope switch in the proper position.
8. Press the charging button and hold in long enough for the capacitors to charge.
9. Release the button and record the deflection on the scope.
10. Calibrate the oscilloscope by adjusting the calibration variacs to obtain the same peak deflection as in 9.
11. Record peak volts and calculate tube voltage or current.

Fig. 3 (T-988567) shows the arrangement of the oscillograph calibrating and switching equipment number "7" and the "off" position may be used to connect the oscillograph to other circuits.

Fig. 4 (T-988567) shows the non-interlocked 110 volt AC supply.

Fig. 5 (T-988567) shows the circuit used to control the voltage regulator.

Fig. 6 (T-988567) shows the interlocked 110 volt AC supply to variacs in the anode, grid, and calibration circuits.

Also included in this folder are the calibration curves for anode and grid supplies, correction curves for the ABLO panel instruments, and some typical tube characteristic curves taken from Livingston's folder.

C. W. Bleichner  
ELECTRONIC TUBE ENGINEERING DIVISION

S. G. Ringland  
ELECTRONIC TUBE ENGINEERING DIVISION

CONNECTION BLOCKS IN REVISED TEST SET

(Can be identified by the number of terminals in each block).

Block 1



- 1) Secondary of transformer
- 2) for CRO calibration
- 3) One side of 110 volt interlocked
- 4) supply
- 5) 110 volt 60 cps. interlock supply
- 6)
- 7) Common for calibration, grid, and anode transformers.
- 8) Calibration variac secondary
- 9) Primary of calibration transformer
- 10) Calibration voltmeter

Block 2

- 1) Primary of 1100 volt transformer
- 2) Secondary of variac for same
- 3) Primary of 6600 volt transformer
- 4) Secondary of variac for same
- 5) Spare
- 6) Spare
- 7) Spare
- 8) DC from control push button
- 9) Spare
- 10) Primary of grid transformers T<sub>5</sub>-T<sub>6</sub>
- 11)
- 12) Primary of grid transformers T<sub>7</sub>-T<sub>8</sub>

Block 3

- 1) 110 volt AC non-interlocked
- 2) supply for peaker
- 3) 110 volt DC ( $\frac{1}{8}$  on block 2)
- 4) Primary of grid transformers T<sub>7</sub>-T<sub>8</sub>



K-5108348

MADE BY *C.W. Bleicher* *M. J. H. H.* INSPECTED BY

GENERAL  ELECTRIC WORKS

**K-5108348**

SHEET No. CONT. ON SHEET

REVISIONS

*Schob*

PRINTS TO


MADE BY - C.W. BLEIGHNER AUG 25

INSPECTED BY - SEPT 4 43


JJ-7858

Calibration for  
Anode Voltage Instruments

K-8639324  
IF SHEET IS READ THIS WAY (HORIZONTALLY), THIS MUST BE TOP.  
IF SHEET IS REVERSE (VERTICALLY), THIS MUST BE LEFT-HAND SIDE.



0-15 Volts  
No. 1306127



0-150 Volts  
No. 1158702

THIS MARGIN RESERVED FOR BINDING.

VT 7  
F


Vac. Tube Engg. Dept.

August 29, 1939

*O. W. Livingston*  
Aug 29, 1939

WL-891  
#25217


GRID CURRENT CHARACTERISTICS



K-6917418

Aug 29-39  
Livingston  
5447





Vac Tube Engrs. Dept.  
August 29, 1939.

*O. W. Livingston*  
Aug 29, 1939

K-6917420


*Aug 29-39  
E. J. Rogers  
M.E. 447*

Vac. Tube Engg. Dept.  
August 29, 1939.

*O. W. Livingston*  
Aug. 29, 1939.

WL-892  
#25516

GRID CURRENT CHARACTERISTICS



K-6917/419


*Aug. 29, 39  
O. W. Livingston  
IN. 8447*

607-2833  
E. J. Cooper  
10-1-34

FN-521-A (9-38)

1/10 Inch Divisions

ANODE AMPERES



ANODE KILOVOLTS

PLATE CHARACTERISTICS

6X4-891  
#25217

Vac. Tube Divs. Dept.  
August 29, 1939  
*W. L. Thompson*  
Aug. 29, 1939.

K-6917422

K-8639326

MADE BY C.W. BLEICHNER AUG 25 43

INSPECTED BY SEPT 4 43

JJ-7888

K-8639326

GENERAL ELECTRIC COMPANY, SCHENECTADY, N. Y., U.S.A.  
IF SHEET IS REVERSED THIS WAY (HORIZONTALLY), THIS MUST BE TOP.  
IF SHEET IS REVERSED THE OTHER WAY (VERTICALLY), THIS MUST BE LEFT-HAND SIDE.

THIS MARGIN RESERVED FOR BINDING.

FN-155 (7-41)  
29/64 inch Divisions

Peak Volts

900/1400

800/1300

700/1200

600/1100

500/1000

400/900

300

200

100

0

0/60

10/70

20/80

30/90

40/100

50/110

60/120

VT 7

AC Voltage

Calibration  
Grid Voltage Supply

August 24, 1943

K-8639326

K-8639323

MADE BY C.W. BLEICHNER

AUG. 25-43

INSPECTED SEPT 4-43

JJ-7858

Calibration For  
Grid Voltage Instruments

Volts to be  
Added

Volts to be  
Subtracted

0-15 Volts  
No. 1252654

Volts to be  
Added

Volts to be  
Subtracted

0-150 Volts  
No. 1310315

VT 7  
F

August 25, 1943

K-8639323

K-8639323

GENERAL ELECTRIC COMPANY, SCHENECTADY, N. Y., U.S.A.  
IF SHEET IS READ THIS WAY (HORIZONTALLY), THIS MUST BE TOP.  
IF SHEET IS RE E OTHER WAY (VERTICALLY), THIS MUST BE LEFT-HAND SIDE.

29/64 inch Divisions  
THIS MARGIN RESERVED FOR BINDING.

29/64 inch Divisions

K-8639327

MADE BY C.W. BLEICHNER AUG. 25-43

INSPECTED BY SEPT. 4-43


JJ-7888

K-8639327

GENERAL ELECTRIC COMPANY, SCHENECTADY, N. Y., U.S.A.  
IF SHEET IS REVERSED (HORIZONTAL), THIS MUST BE TOP.  
IF SHEET IS REVERSED (VERTICAL), THIS MUST BE LEFT-HAND SIDE.

THIS MARGIN RESERVED FOR BINDING.

FN-155 (4-41)  
29/64 inch Divisions



Calibration  
Anode Supply Voltage

AC Voltage

Peak Volts

August 24, 19

K-8639327

V7  
F


Calibrations For  
Peak Reading Instruments JJ-7858

Volts to be  
Added

0.1

Volts to be  
Subtracted

0.1



0.7.5 Peak Volts  
No. 1255550

K-8639325  
GENERAL ELECTRIC COMPANY, SCHENECTADY, N. Y., U.S.A.  
IF SHEET IS READ THIS WAY (HORIZONTALLY), THIS MUST BE TOP.  
IF SHEET IS RI IE OTHER WAY (VERTICALLY), THIS MUST BE LEFT-HAND SIDE.

THIS MARGIN RESERVED FOR BINDING.

VT 7  
F