



RADIO CORPORATION OF AMERICA

RCA VICTOR DIVISION
TUBE DEPT. STANDARDIZING

HARRISON, N. J. LANCASTER, PA. EEE

SUBJECT APPROVED LUBRICANTS FOR MATERIALS
FORMED INTO PARTS

DATE May 12, 1949 PAGE 1

STANDARDIZING
NOTICE 34-29-1A

SUPERSEDED DATE 3/14/47

All purchased fabricated parts & assemblies shall use no lubricants other than the following STANDARD LUBRICANTS:

1. Butyl Carbitol Acetate (Carbide & Carbon Chemical Co.)
2. Semi-Fluid Vastolein - T (G. Whitfield Richards Co.)
3. No. 6603-2 Extreme Pressure Drawing Compound (Standard Oil Co.)
4. Varsol (Standard Oil Co.)
5. Sunoco Spirits (Sun Oil Co.)
6. N-A-L Oil (G. Whitfield Richards Co.)
7. 600-W Oil
8. Cadet W Oil (Sinclair Refining Co.)
9. Castor Oil
10. Mineral Machine Oil (SAE 30)
11. No Lubricant
12. Fiske No. S-130 (Fiske Bro's. Refining Co.)
- *13. No. 24 Slushing Oil (Standard Oil Co. of Ohio)

Any deviations must first be approved by our laboratory.

This control is necessary for the proper cleaning of the parts prior to their use.

Note: For more explicit instructions for use in RCA Plant see Stdzg. Not. 34-29-1.

ENGINEERING SECTION
STANDARDIZING

1-495-9-60 35 - 121/bw